

APPLICATION  
  
FOR  
  
UNITED STATES LETTERS PATENT

TITLE: INFLATABLE BED

INVENTOR: HSIN-TSAI WU

Express Mail No.: EV372703174US

Date: May 19, 2004

## INFLATABLE BED

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

5 The invention relates to an inflatable bed, more particularly to an inflatable bed that has a rounded outer periphery and a varying height.

#### 2. Description of the Related Art

Referring to Figure 1, a currently available inflatable bed 1 is rectangular in shape after being  
10 inflated. The inflatable bed 1 includes bottom and top sheet layers 11, 12, a surrounding sheet 13 that interconnects end peripheries 111, 121 of the bottom and top sheet layers 11, 12 and that cooperates with the bottom and top sheet layers 11, 12 to confine an  
15 air chamber 16, a plurality of tension members 14, and an air valve 15. The tension members 14 have substantially same heights, and are disposed uniformly in the air chamber 16 along the length of the inflatable bed 1. Two ends of each of the tension members 14 are  
20 connected respectively to the bottom and top sheet layers 11, 12. The air valve 15 is in fluid communication with the air chamber 16 for inflation and deflation of the inflatable bed 1. However, this kind of rectangular inflatable bed 1 has a monotonous and dull appearance.  
25 Furthermore, when the middle portion of the inflatable bed 1 is pressed by the body weight of the user during use, air is forced to flow to the four corners of the

inflatable bed 1 such that the middle portion of the bed 1 cannot maintain sufficient stiffness to provide a good supporting effect. Sleeping quality of the user is thus adversely affected, thereby leading to sores and aches in the waist and back of the user.

In addition, the inflatable bed 1 has the same height between the bottom and top sheet layers 11, 12, as shown in Figure 2, so that the bed 1 has a uniform height after being inflated. When the user lies on the inflatable bed 1, a pillow 18 is necessary so as to conform to the physiological demand, that is, the head should be higher, whereas the feet should be lower. However, the pillow 18 only increases the burden of the user during an outdoor trip such that use of the inflatable bed 1 is somewhat inconvenient.

#### **SUMMARY OF THE INVENTION**

Therefore, the object of the present invention is to provide an inflatable bed that has a rounded outer periphery, that has a uniform stiffness to provide stable support, and that has a varying height to ergonomically fit the body of a user.

According to this invention, an inflatable bed comprises a bottom sheet layer having a first peripheral end, a top sheet layer disposed above the bottom sheet layer and having a second peripheral end, a surrounding sheet that interconnects the first and second peripheral ends and that cooperates with the bottom and top sheet

layers to form a bed body which defines an air chamber,  
a plurality of spaced-apart tension members disposed  
within the air chamber, and an inner partition sheet  
disposed within the air chamber and spaced apart from  
5 and surrounded by the surrounding sheet. Each of the  
tension members has two ends connected respectively to  
the bottom and top sheet layers. The inner partition  
sheet is connected to the bottom and top sheet layers  
so as to divide the air chamber into a first air chamber  
10 and a second air chamber surrounded by the first air  
chamber. The first air chamber is defined between the  
surrounding sheet and the inner partition sheet.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Other features and advantages of the present  
15 invention will become apparent in the following detailed  
description of the preferred embodiments with reference  
to the accompanying drawings, of which:

Figure 1 is a perspective view of a currently  
available inflatable bed, in which a portion of the  
20 interior thereof is exposed for the sake of clarity;

Figure 2 is a schematic side view of the inflatable  
bed of Figure 1 in a state of use;

Figure 3 is a perspective view of a preferred  
embodiment of an inflatable bed according to the present  
25 invention, in which a portion of the interior thereof  
is exposed for the sake of clarity;

Figure 4 is a schematic side view of another

embodiment of an inflatable bed according to the present invention;

Figure 5 is a schematic side view of still another embodiment of an inflatable bed according to the present invention;

Figure 6 is a perspective view of a further embodiment of an inflatable bed according to the present invention, in which a portion of the interior thereof is exposed for the sake of clarity; and

Figure 7 is a perspective view of yet another embodiment of an inflatable bed according to the present invention, in which a portion of the interior thereof is exposed for the sake of clarity.

#### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

Before the present invention is described in greater detail, it should be noted that like elements are denoted by the same reference numerals throughout the disclosure.

Referring to Figure 3, a preferred embodiment of an inflatable bed 20 according to the present invention is shown to comprise a bottom sheet layer 21, a top sheet layer 22, a surrounding sheet 23, an inner partition sheet 24, a plurality of tension members 25, and an air valve 26.

The bottom sheet layer 21 has an oval-shaped first peripheral end 211.

The top sheet layer 22 is disposed above the bottom

sheet layer 21, and has an oval-shaped second peripheral end 221 that corresponds to the first peripheral end 211.

5 The surrounding sheet 23 interconnects the first and second peripheral ends 211, 221 of the bottom and top sheet layers 21, 22, and cooperates with the bottom and top sheet layers 21, 22 to form a bed body 27 which defines an air chamber 271.

10 The tension members 25 are disposed within the air chamber 271. Each of the tension members 25 has two ends 251, 252 connected respectively to the bottom and top sheet layers 21, 22. The function of the tension members 25 is to maintain a proper distance between the bottom and top sheet layers 21, 22 of the inflatable bed 20 after the latter is inflated.

15 The air valve 26 is in fluid communication with the air chamber 271 for inflation and deflation of the inflatable bed 1.

20 The inner partition sheet 24 is disposed within the air chamber 271, and is spaced apart from and surrounded by the surrounding sheet 23. The inner partition sheet 24 is connected to the bottom and top sheet layers 21, 22, thereby dividing the air chamber 271 into a first air chamber 2711 and a second air chamber 2712 surrounded by and in fluid communication with the first air chamber 2711. The first air chamber 2711 is defined between the surrounding sheet 23 and the inner partition sheet 24.

After the inflatable bed 20 is inflated, the bed 20 has the oval top sheet layer 21 surrounded by the surrounding sheet 23 so that the bed 20 will not have sharp corners such as those found in the currently available inflatable bed 1 (see Figure 1). When a user lies on the top sheet layer 21, air in the middle portion of the bed 20 will not flow to corners, but will instead provide a uniform support at the middle portion, thereby resolving the drawback encountered in the currently available inflatable bed 1 (see Figure 1) so that the sleeping quality of the user is enhanced. At this time, the first air chamber 2711 is formed as an air peripheral ring surrounding a periphery of the inflatable bed 20, and serves to reinforce the inflatable bed 20 so that the user is prevented from falling off the bed 20.

In another embodiment of the present invention, as shown in Figure 4, the bed body 27 includes an upper body support portion 272, a lower body support portion 274, and a juncture 203 between the upper and lower body support portions 272, 274. The upper body support portion 272 has a first end 201. The lower body support portion 274 has a second end 202 opposite to the first end 201. The juncture 203 is located substantially below a part of the upper body of the user 30 adjacent to the shoulder when the user lies normally on the inflatable bed 20, and the length of the upper body support portion 272 is around one-third of the length of the inflatable bed

20 measured from the first end 201. The tension members 25 in the bed body 27 are adjusted during the production of the inflatable bed 20 so that the lengths of the tension members 25 in the upper body support portion 272 increase gradually from the juncture 203 toward the first end 201, while the lengths of the tension members 25 in the lower body support portion 274 are maintained uniformly from the juncture 203 toward the second end 202, and are shorter than those in the upper body support portion 272. As such, the height 205 of the bed body 27 at the first end 201 is greater than the height 206 of the bed body 27 at the second end 202 after the bed body 27 is inflated. An inclined support face 275 extends from the juncture 203 to the first end 201, and functions as a pillow so that the inflatable bed 20 conforms ergonomically to the body of the user.

In still another embodiment of the present invention, as shown in Figure 5, the upper body support portion 272 of the inflatable bed 20 has a head region 2721 proximate to the first end 201, and a chest region 2722 proximate to the juncture 203. The lengths of the tension members 25 in the upper body support portion 272 increase gradually from the juncture 203 toward the chest region 2722, and maintain a uniform length from the head region 2722 toward the first end 201. An inclined support face 207 extends in the chest region 2722 between the juncture 203 and the head region 2721. An integral pillow is thus



formed in the upper body support portion 272.

In a further embodiment of the present invention, as shown in Figure 6, the inflatable bed 20 further comprises first and second partition sheets 29, 28, and a reinforcing sheet 255. The first and second partition sheets 29, 28 confine a third air chamber 273 formed within the second air chamber 2712 in the upper body support portion 272. The first partition sheet 29 has top and bottom ends connected respectively to the top and bottom sheet layers 22, 21 and extending substantially along a first direction transverse to a line that extends from the first end 201 to the second end 202. The second partition sheet 28 is substantially U-shape, and has top and bottom ends connected respectively to the top and bottom sheet layers 22, 21, and two opposite ends 281 connected respectively to the first partition sheet 29. The third air chamber 273 is in fluid communication with the second air chamber 2712, and serves to function as a hidden pillow in this embodiment. The reinforcing sheet 255 extends along the first direction, and is disposed within the third air chamber 273. The reinforcing sheet 255 is connected to the second partition sheet 28 so as to divide the third air chamber 273 into two compartments 2731, thereby reinforcing the supporting function of the third air chamber 273.

In yet another embodiment of the present invention,

as shown in Figure 7, the inflatable bed 20 further comprises first and second partition sheets 29, 28, and a plurality of reinforcing sheets 256. The first and second partition sheets 29, 28 confine a third air chamber 273 formed within the second air chamber 2712 in the upper body support portion 272. The first partition sheet 29 has top and bottom ends connected respectively to the top and bottom sheet layers 22, 21 and extending substantially along a first direction transverse to a line that extends from the first end 201 to the second end 202. The second partition sheet 28 is substantially U-shape, and has top and bottom ends connected respectively to the top and bottom sheet layers 22, 21, and two opposite ends 281 connected respectively to the first partition sheet 29. The third air chamber 273 is in fluid communication with the second air chamber 2712, and serves as a hidden pillow. The reinforcing sheets 256 extend along a second direction transverse to the first direction, and are disposed within the third air chamber 273. The reinforcing sheets 256 are connected to the first and second partition sheets 29, 28 so as to divide the third air chamber 273 into a plurality of compartments 2732.

While the present invention has been described in connection with what is considered the most practical and preferred embodiments, it is understood that this invention is not limited to the disclosed embodiments

but is intended to cover various arrangements included within the spirit and scope of the broadest interpretation so as to encompass all such modifications and equivalent arrangements.